

MOUNTED TYPE ROBOT ROTATING HEAD MODEL TURBO ATOMIZER



SMTA-600



SMTA-600



SMTA-600



GENERAL FEATURES

It has polyester and polyethylene depot and membrane pumps, which are operated by power take-off from tractor conveys pressuring chemical liquid to nozzles on fan. Fan is also operated with power- take off and it sends pressured air out. Pressured chemical liquid is sprayed by adjustable nozzles around the fan by air circulation. Atomization is provided on right or left sides by remote control.

TECHNICAL DETAILS

CODE	CAPACITY (LT)	MATERIAL OF DEPOT	TYPE OF FAN	PUMP	NUMBER OF DIAPHRAGM PISTON	FLOW RATE (LT/MIN.)	PRESSURE (BAR)	PTO ROTATION (RPM)
SMTA-600	600	PLASTIC	ROBOT ROTATING HEAD	S-105	4	105	50	540
SMTA-800	800	PLASTIC	ROBOT ROTATING HEAD	S-105	4	105	50	540





SOIL MASTER
AGRICULTURAL MACHINERY

HEAD OFFICE

Add: Fevzi Cakmak Mh. 10758 Sk. No: 16/G
42050 Karatay/Konya/TURKEY

T: +90 332 290 00 20
F: +90 332 290 00 19

FACTORY

Add: Büyükkayacık Osb, Yaylacık Cd. No:
23, 42250 Selcuklu/Konya/TURKEY

T: +90 332 239 18 85
T: +90 332 239 18 86
F: +90 332 239 18 87

www.soilmaster.com.tr



+90 (532) 137 01 74



info@soilmaster.com.tr



SOILMASTER AGRICULTURAL MACHINERY



For detailed information about
our products, you can scan the
QR code by your device.